

DFPUR-355

It is used to thin polyurethane products and/or clean equipment.

■ ADVANTAGES

It is used as a thinner for solvent polyurethane systems. It is not used as a thinner in solvent-free polyurethane systems, it is only used for cleaning.

■ SCOPE OF APPLICATION

It is used in the mixing ratios specified in the technical bulletin or label information of the product to be used.

■ CONSUMPTION

Minimum toplam tüketim: 0,7-0,9 kg/m²

■ STORAGE

Packaging	15 lt
Colour	-
Shelf Life	It should be stored between 5-35 °C in sealed packages away from direct sunlight. The mouth of the containers must be kept closed when not in use. It should be protected from frost. Shelf life 12 Months.

■ WARNINGS AND RECOMMENDATIONS

Flammable, products should be kept away during application. There should be no smoking. Care should be taken to ensure constant ventilation of the application area. Protective equipment such as glasses and gloves should be used during application. In case of eye contact, wash thoroughly with plenty of water. For detailed information, please request the Material Safety Data Sheet. It should be kept out of reach of children. The product should be consumed by professional users, taking into account the data in the technical information section.

All technical information stated in this product data sheet is based on laboratory tests. Actual values may vary due to circumstances beyond our control.

İZERSAN YAPI MALZ.SAN VE TİC.LTD.ŞTİ.

Center Factory: Egemenlik Mah. 6016/6 Sk. No:19/1 İşikkent Bornova/ İZMİR

www.dryfix.com.tr - info@izersan.com.tr

Tel&Fax: +90 850 777 05 35



DFPUR-355

■ TECHNICAL SPECIFICATIONS AND PERFORMANCE VALUES

Colour	Colorless
Intensity	ASTM D1475 / DIN 53217 / ISO 2811, 20°C 0,83-0,87 g/ml
Flash Point	ASTM D 93 17

The technical specifications written above were written according to the test results performed under 23°C and 50% relative humidity conditions. Values may vary under different temperature and humidity conditions.

■ SAFETY PRECAUTIONS

During use and storage, appropriate work clothes, glasses, gloves and masks should be used for worker health and safety. Eye, mouth and skin contact should be avoided. The contacted area should be washed with clean of water. In more dangerous situations or if the product is swallowed, a specialist doctor should be consulted immediately. Food and drink should not be allowed into application areas. It should be kept out of reach of children. For detailed information, the Safety Data Sheet (SDS) should be consulted.

All technical information stated in this product data sheet is based on laboratory tests. Actual values may vary due to circumstances beyond our control.

■ LEGAL WARNING

Applications that may occur if the product is used for purposes other than its intended purpose or if the above-mentioned conditions are not complied with: from the mistakes of İzersan Yapı Malz. San. Ve Tic. Ltd. Şti. is not responsible.

İZERSAN YAPI MALZ.SAN VE TİC.LTD.ŞTİ.

Center Factory: Egemenlik Mah. 6016/6 Sk. No:19/1 İşikkent Bornova/ İZMİR

www.dryfix.com.tr - info@izersan.com.tr

Tel&Fax: +90 850 777 05 35

