

FUNCTIONAL SOLUTIONS FOR BUILDINGS

Technical Data Sheet

Date of Revision: 26.08.2025

Revision Number: 001

ADERANS

Dryfix Aderans is a polymer-based, ready-to-use primer developed for new ceramic applications on ceramic surfaces, providing high adhesion. Thanks to its special formula, it provides excellent adhesion on low-absorption surfaces and prevents ceramics from falling off.

AREAS OF USE

- Ceramic-on-ceramic applications.
- Low-absorption surfaces such as granite, marble, porcelain, and glass mosaic.
- Bathroom, kitchen, and outdoor ceramic floor covering applications.

ADVANTAGES

- High adhesive strength.
- Ready-to-use formula.
- Fast drying.
- Easy to apply with a brush or roller.
- Solvent-free, environmentally friendly.

WARNINGS

- Do not apply to damp or wet surfaces.
- After using the product, use a ceramic adhesive of at least C2TE Class (Dryfix Cer 606) or higher.

APPLICATION INSTRUCTIONS

- The surface must be clean, dry and free of dust.
- Mix the contents of the package without adding water until homogeneous.
- Dryfix Adhesion can be applied using a brush, roller, or airless sprayer.
- Apply the product evenly over the entire surface.
- After the product has dried (approx. 4 hours), ceramic adhesive application can proceed.

TECHNICAL SPECIFICATIONS

- Appearance: Transparent pink
- Drying Time: Minimum 4 hours (depending on ambient temperature)
- Application Temperature: Between +5°C and +30°C.
- Consumption: 100-200 g/m²

STORAGE

Store in a dry and cool place in its original packaging. Protect from freezing. Unopened packaging can be stored for 12 months from the production date.

SAFETY WARNINGS

Store out of reach of children. Avoid contact with skin and eyes. Ensure adequate ventilation during use. For detailed safety information, refer to the SDS (Safety Data Sheet).

LEGAL NOTICE

IZERSAN YAPI MALZEMELERİ SAN. VE TİC. LTD. ŞTİ.,

is not responsible for any application errors that may arise due to the product being used for purposes other than its intended use or failure to comply with the conditions specified above.

All technical information specified in this product data sheet is based on laboratory tests. Actual values may vary due to conditions beyond our control.



İZERSAN YAPI MALZEMELERİ SAN. VE TİC. LTD. ŞTİ.

Headquarters: Folkart Towers A Kule No:47 K:28/2809 Bayraklı / İZMİR **Factory:** Egemenlik Mah. 6016/6 Sk. No:19/1 Işıkkent Bornova / İZMİR

Tel.: 0 850 777 05 35

